



PRODUCT DATA SHEET



Protection Board BP-AspPB

Description

BP-AspBP protection board is a semi-flexible core board, composed of a mineral fortified asphaltic core between two outside layers of asphalt impregnated fiberglass mat.

Use

BP-AspBP provides protection to the rubberized asphalt waterproofing membrane from damage by backfill or construction traffic. Typical applications include plaza decks, roof terraces, promenade decks, pedestrian concourses, tunnels, concrete bridge decks and parking garage decks.

Features

Absorbs the impact of placing concrete or laying asphalt concrete and regular job site traffic on waterproofed slabs.

Installation Notes

Install the protection boards to form a continuous protective layer over the membrane waterproofing. Sheets are easily cut with a roofer's knife for fitting around protrusions.

If the protection board is to be nailed to a vertical surface, obtain membrane manufacturer's approvals and recommendations for sealing resulting membrane punctures.

Use only rubber tired construction equipment on the protection board.

It is advisable to cover the protection board as soon as possible. This limits the exposure of the waterproofing system to continuous job site damage.

Typical Dimensions

Nominal Thickness: 3.6 ± 0.4 mm

Sheet Size: 914 mm x 1.5 m (36' x 60')

Weight: 4.26 kg/m² (87 lb/100 ft²)

(Other thicknesses may be available upon request)